

# APOLLO 66

Pneumatic Airless Piston Pump

CE Ex II 2GT6 X

Pneumatic airless piston pump for high pressure professional paint spraying, suitable for treating paint and anti-corrosion with high viscosity products.



## CODE

## DESCRIPTION

TKP6618C APOLLO 66 Pneumatic airless piston pump C/ Trolley - Pressure regulator - Stainless steel inline filter - HP hose 10m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system

TKP6618A APOLLO 66 Pneumatic airless piston pump C/ Trolley - Pressure regulator - Stainless steel inline filter - Complete suction system

TKP6618B APOLLO 66 Pneumatic airless piston pump on bracket - Pressure regulator - Stainless steel inline filter

TKP6618D APOLLO 66 Pneumatic airless piston pump C/ Stainless steel inline filter

## Technical specifications

Ratio: **66:1**

Pump Capacity per cycle: **cm<sup>3</sup> 100**

Stroke: **mm 100**

Max Delivery Free Flow: **ltr/min 15**

Number of stroke per liter: **10**

Max. Working outlet Pressure: **Bar (psi) 528 (4640)**

Max. Air Inlet Pressure: **Bar (psi) 8 (116)**

Weight: **kg. 64**

Air Consumption: **ltr/min 600-2650**

Packing type: **Fix**

Material inlet fitting size: **M 36x2 mm**

Material outlet fitting size: **M 16x1,5 mm**

Packing material: **PTFE-PE-LEATHER**